

LUMEN WARM



**EROS SUSPENDED
LWERS-SPD**



BROCHURE



INSTALLATION SHEET



Eros Suspended

The Eros conception allows you to create long linear runs to appropriately light up the space it is installed in. Custom lengths and patterns are also a possibility and with its fully lit corners, darkness will be a thing of the past



Performance

Direct			
Lm	Lens Type	W/ft	Lm/W
300	Lambertian	2.4	125
750		6.1	122
1000		8.8	114
750	Multicell 12° Module	5.1	147
750	Multicell 24° Module	5.1	147
750	Multicell 38° Module	5.1	147
750	Multicell 50° Module	5.1	147
750	Multicell 35°X70° Module	5.1	147


Indirect			
Lm	Lens Type	W/ft	Lm/W
1000	Lambertian	4.8	408
750	60°	3.3	233
750	90°	3.3	233
750	Asymmetric	3.3	233
750	Batwing	3.3	233

Please note this information is based on a 1ft / 4000K fixture.

Highlights


Lumen Output	Up to 1100lm/ft Deliver lumen with lambertian lens.
Efficiency	Up to 145lm/W
Colour Temperature	2700K, 3000K, 3500K, 4000K
CRI	90
Input Voltage	Integral driver, 100-277VAC
Dimming Options	0-10V (Down to 1%), Lutron Ecosystem, Dim to Off
Lead In	Up to 80ft maximum run per power feed (15A /1650W maximum).

Dimensions




Distribution


Direct




Indirect




Configuration Example




ACCENT SPOTLIGHT



LAMBERTIAN MODULE



MULTICELL MODULES



PATTERNS
MULTIPLE OPTIONS

LUMEN
WARM

TOLL FREE 1 866 586 3692
TEL. 514 286 0227
info@lumenwarm.com

OFFICE AND SHOWROOM
155 Fortin Street, Suite 180, Quebec
City, QC G1M 3M2, Canada

LAST UPDATE
22/10/2024

The information herein may be changed without notice. Please consult our Terms and Conditions. <https://lumenwarm.com/en/terms-and-conditions/>

Ordering Sections	Technical Information	Controls	Mounting Options	Emergency	Photometrics Data
-------------------	-----------------------	----------	------------------	-----------	-------------------

Eros Suspended

Ordering Guide

Ex : LWERS-SPD-48-NA-MBK-MC12-DCH-P300

Product Code	Length	Pattern Type	Pattern Dimensions	Exterior Finish	Direct Linear Modules (3)	Multicell Finish	Direct Linear Modules Lumen Package
LWERS-SPD							
	48 48in 60 60in 72 72in 84 84in 96 96in 144 144in CUCR Custom Continuous Run CUSU Custom Single Unit CUPA Custom Pattern	PAL L-Shaped Pattern PAS Square Shaped Pattern PAU U-Shaped Pattern PAT T-Shaped Pattern PAX X-Shaped Pattern PAH H-Shaped Pattern CU Custom Shaped Pattern (1) NA None	A X B A X B A1+A2 X B A X B X C A1+A2 X B1+B2 A X B1+B2 X C1+C2	MBK Matte Black MWH Matte White CU Custom (2)	LM High Efficiency Lambertian Lens MC12 12° MC24 24° MC38 38° MC50 50° MC3570 35° x 70° NA None	DCH Dark Chrome MBK Matte Black MWH Matte White CU Custom NA None	P300 300lm/ft P400 400lm/ft P600 600lm/ft P700 700lm/ft P900 900lm/ft P1100 1100lm/ft CU Custom Output (4)
Refer to the 'Technical Information' section for further details.		(1) A drawing will be needed for custom shapes. Refer to next page for more details on available shapes.		(2) Specify RALK7 code.		*The Multicell Module (MC) option is required to select this option*	
				(3) Full length direct light module (1 choice of direct module only)		(4) Consult factory for more information.	

Ex : 27K-ULFR-P300-27K-BKD-FRG-MBK-9SK

Direct Colour Temperature	Indirect Linear Modules	Indirect Lumen Package	Indirect Colour Temperature	Power Cable Colour	Canopy and Finish	Accessories
27K 2700K 30K 3000K 35K 3500K 40K 4000K ADJ Tunable White CU Custom (5)	ULFR High Efficiency Lambertian Lens UL60 60° Focus Lens UL90 90° Focus Lens ULDP Asymmetric Lens ULSP Batwing Lens NA No Indirect Module (6)	P300 300lm/ft P400 400lm/ft P600 600lm/ft P700 700lm/ft P900 900lm/ft P1100 1100lm/ft CU Custom Output (7) NA None	27K 2700K 30K 3000K 35K 3500K 40K 4000K CU Custom (8) NA None	BKD Black Decorative Cable MWH White Decorative Cable	FRD-MBK Matte Black Round FRD-MWH Matte White Round FRG-MBK Matte Black Rectangle (9) FRG-MWH Matte White Rectangle (9) CU Custom (10)	3SK 3ft Adjustable Suspension Kit 9SK 9ft Adjustable Suspension Kit 20SK 20ft Adjustable Suspension Kit CUSK Custom Length (11)
(5) Consult factory for more information.	(6) A colour matching cover will be used to protect the inside components if no indirect lighting is required	(7) Consult factory for more information.	(8) Consult factory for more information.		(9) Rectangular Canopy is compatible with G82020 junction box models. Refer to the "Mounting Options" section for details. (10) Specify the desired canopy and the RALK7 code.	(11) Specify cable length.

Ex : IHC-NA-UNI-X10V-1C-NA-AWNR


Mounting	Optional Accent Spotlights (12)	Voltage	Driver	Circuits (16)	Emergency (17)	Controls (18)
916 9/16 T-Grid Clip 1516 15/16 T-Grid Clip IHC Hard/Drywall Ceiling	18GL Single Unit, Power Feed Side 18GO Single Unit, Opposite Side 28GE Two Units at Extremities NA None	UNI Universal 100-277V 347 347V (13)	X10V 0-10V Driver 1% Z10V 0-10V Driver Dim to Off DA2 Dali 2.0 (14) LTI Lutron Hi-Lume 1% OTH Other (15)	1C One Circuit 2C Two Circuits CU Custom	B6W Integral Battery Pack 6W B10W Integral Battery Pack 10W NA None	AWNR Athena Wireless Node RF Only AWNS Athena Wireless Node RF + Occupancy Sensor NA None
	(12) See P.5 for more ordering details and sketch/drawing for spotlight placement.	(13) Requires 0-10V driver.	(14) Dali driver commissioning is required. (15) Consult factory for more information.	(16) Refer to the "Controls" section for more details.	(17) Provide a sketch/drawing for the positioning of the emergency section. Refer to the "Emergency" section for further details. (Not compatible with 347V).	* Only one Node per Circuit.* (18) Athena not compatible with 347V.

Notes


Patterns

Base Information


Description	The Eros family offers 3 standard connector shapes for different pattern configurations. Every connector is welded in factory and is fully illuminated, ensuring consistent lighting for seamless installation.
Dimensions	L-Shaped Connector : 7.5in x 7.5in / 190.5mm X 190.5mm
	T-Shaped Connector : 7.5in x 13.75in / 190.5mm X 332mm
	X-Shaped Connector: 13.75in x 13.75in / 332mm X 332mm




Square Shaped Pattern representation




L-Shaped Pattern	
A	B
36in Minimum length	
PAL= A X B	




U-Shaped Pattern		
A	B	C
36in Minimum length		42in Minimum length
PAU= A X B X C		




Square Shaped Pattern	
A	B
42in Minimum length	
PAS= A X B	



X-Shaped Pattern			
A1	A2	B1	B2
36in Minimum length			
PAX= A1 + A2 X B1 + B2			




T-Shaped Pattern		
A1	A2	B
42in Minimum length		36in Minimum length
PAT= A1 + A2 X B		



H-Shaped Pattern				
A	B1	B2	C1	C2
42in Minimum length		36in Minimum length		
PAH = A X B1 + B2 X C1 + C2				

Workshop Drawing

Use grid to draw Custom Pattern




Accent Spotlights

Ordering Options


Example : 1BGL-MBK-P400-27K-16-NA-IC

Product Code	Spotlight Code	Finish	Lumen Package	Colour Temperature	Optics	Accessories	Circuit
LWERS							
	1BGL Single Unit, Power Feed Side 1BGO Single Unit, Opposite Side 2BGE Two Units at Extremities NA None	MBK Matte Black MHW Matte White	P400 400lm/ Spotlight P800 800lm/ Spotlight	27K 2700K 30K 3000K 35K 3500K 40K 4000K CU Custom	16 16° 26 26° 36 36°	DIFF Frosted Diffuser HL Hex Louver NA None	IC Indirect Circuit DC Direct Circuit SC Separate Circuit (1)
							(1) Adds a circuit on the fixture, consult factory for more information.


Dimensions




Performance



Features



Accent Spotlight Positioning




Technical Information


Construction

Aluminum Profile	100% Recycled Aluminum grade 6063-T5
Endcap	Aluminum grade 6063-T5, Extruded and machined part
Brackets	
High Efficiency Lambertian Lens	Frosted Acrylic, Extruded part
Suspension Cable	Stainless steel adjustable aircraft cable
Joiner	1060 Steel, 14 gauge

Aluminum Profile Colour



MBK - Matte Black




MWH - Matte White




CU - Specify RALK7 colour


Dimensions




Indirect & Direct Lambertian Lens




Indirect 60° Lens Direct Lambertian Lens



Indirect 90° Direct Lambertian Lens



Indirect Asymmetric Lens Direct Lambertian Lens



Indirect Batwing Lens Direct Lambertian Lens

Length Management




- A
- Minimum length for Eros is 4ft long.
Eros longer than 8ft will have an additional cost for shipping purpose.
Maximum length for one fixture is 12ft.
Fixture over 12ft long will be split into sections (see Mounting Options section).
- B
- All Suspension cables are field adjustable in length.

Module Management


LM -High efficiency Lambertian Lens Module

- Dimensions
- Maximum length for lens : 3657.6mm/144in
Minimum length for lens: 152.4mm/6in
- Management
- Lambertian module must be calculated with ≈ 152.4mm/6in increment to reduce dark spot risk.




MCXX-Multicell Modules

- Dimensions
- Direct Multicell module is ≈ 190.5mm/7.5in
- Management
- Measure 190.5mm/7.5in increment when you plan your section in the fixture to avoid visible spacing.



Multicell Optics




Driver

0-10V Driver 1%	Driver for maximum dimming capabilities. Provide a smooth dimming from 10% up to 0.1%, works on 347V only.
0-10V Driver Dim to Off	Driver that facilitates the control of dimming of maximum light power to off state, operates only on 347V.
Dali	Driver which allows the addressability of luminaires to be adapted individually or in groups. Its system facilitates the management of connections as well as its installation.
Lutron Hi-Lume 1%	The Hi-Lume LED driver is the world's first LED driver to offer smooth, continuous 1% dimming for virtually any LED fixture.  Lutron Hi-Lume 1% Spec Sheet
Other Driver	Other driver options are available. Consult factory for more information.


Circuits

1 Circuit




All lighting is on the same circuit and will be controlled simultaneously.

2 Circuits



Direct and indirect lighting are on two separate circuits and will be controlled independently.



(CU) More than 2 Circuits



Direct and indirect lighting are on two separate circuits and will be controlled independently.

A third circuit is added to the fixture to specifically control the accent spotlight when the Separate Circuit (SC) option is selected in the Accent Spotlight ordering guide.


Athena Wireless Node

Models	AWNRR – Radio Frequency	AWNS – Radio Frequency + Occupancy Sensor
Description	The Athena wireless node is a radio frequency (RF) device that enables simple, digital control of individual light fixtures in an Athena controlled system. The small size and compatibility with a wide variety of drivers allow for seamless integration with common commercial lighting fixtures from any manufacturer.	
Driver Compatibility	Static White Control: • Lutron digital drivers (coming soon) • DALI-2 certified drivers • ANSI C137.1 compliant 0-10V drivers Tunable White Control : • Lutron digital drivers (coming soon) • DALI-2 certified drivers	
Power / Load	• IEC SELV / NEC® Class 2 • Operating voltage: 9.5 – 28.8V • Operating current: 46mA max	
Spec Sheet		Installation Documents 
Finish	Node colour will match the fixture finish, if custom colour is selected, black node will be supplied unless specified otherwise.  AWNRR – Matte White AWNRR – Matte Black AWNS – Matte White AWNS – Matte Black	


Mounting Options

Canopy Options


Round Canopy		
Code	FRD-MBK	FRD-MWH
Description	Matte Black Round Canopy	Matte White Round Canopy
Dimensions	Ø5inL x 0,28inH	
Boîte de Jonction	Compatible with the Standard octagonal model 4.5in x 4.5in	




Rectangle Canopy		
Code	FRG-MBK	FRG-MWH
Description	Matte Black Rectangle Canopy	Matte White Rectangle Canopy
Dimensions	2.90inW X 6.55inL x 0.60inH	
Boîte de Jonction	Compatible with rectangular model: BC 1104LH1/1104L-CRT/GB 2020 or equivalent.	



Detailed View



Canopy Options, Hard / Drywall Mounting :
With power feed cable




Hard / Drywall Mounting : No power feed cable

Canopy Installation




Canopy Installation Instructions
Consult our installation guide for more information.

Cable Colour




BKD
Black Decorative Cable
(Pass-Through Is Matte Black)


WHD
White Decorative Cable
(Pass-Through Is Matte White)



Round Canopy on T-Grid: With power feed cable




9/16 Clip for T-Grid : No power feed cable




15/16 Clip for T-Grid: No power feed cable

Dimensions




Power feed cable and adjustable aircraft cable measurement from edge.




Adjustable aircraft cable measurement from edge.

Joiner Information



Align the Fixtures
Connect the wires/pin connector and use steel aligners to fuse sections.
Splicing connectors are included for the section connection



Secure the Fixtures
Secure the two fixtures together by tightening the screws of the joining plate.


Suspension Cable Options

Fixture Singe Unit




Suspension Cables	Only two suspension cable are needed for this options.
Weight	Eros weight /feet : 1.5lbs

Fixture Multiple Sections



Suspension Cables	For each section, an additional suspension cable will be added at its junction.
Custom Length	Contact our factory for more information on custom length and its specifications.



Secure the Alignment
Tighten the set screws with an Allen key to secure the fixture's alignment.







Single Unit Installation Guide
Consult our installation guide for more information.



Multiple Sections Installation Guide
Consult our installation guide for more information.

Light Colour Data



Eros IES



Light Loss Factor

4000K	0%
3500K	8%
3000K	17%
2700K	21%
2400K	24%
1800K	26%