

1150lm/ft Static White LED Strip

Lumen Warm's high efficacy series is a high output and high efficiency range of LED strips. They offer 90+ CRI with outputs as high as 1400 lumens per foot and up to 160 lumens per watt.




Highlights

Colour Temperature	2700K, 3000K, 3500K, 4000K	Input Voltage	24VDC
CRI*	90+ 2 Step MacAdam Ellipse	Consumption	7.31W/ft 24W/m
Lumen Output	1148lm/ft 3768lm/m	Dimming Options	ELDR, DIM, DMX, DALI 2, DALI 2 + Athena Node, Lutron
Lumen/Watt	157lm/W	Mounting	3M VHB premium quality double-sided tape
Driver	Remote Driver; 100-277V	Applications	Dry or damp environment, high output light fixtures, millwork, cove, shelves, displays, handrails and much more
Working Temperature	-20°C ~ 60°C / -4°F ~ 122°F		

*Please note this information is based off a 4000K LED Source.

*Please note this information is based off a 4000K LED Source.

Dimensions




Ordering Options

Ex : LWHE1150-5m-27K-NA-NA

Product Code	Length	Colour Temperature	Lead In	Lead Out
LWHE1150	5m 25m CU Custom (0)	27K 2700K 30K 3000K 35K 3500K 40K 4000K CU Custom	DC7IN FT6 DC Quick Connect 7in DC3FT FT6 DC Quick Connect 3ft FT43FT FT4 Cable 3ft TC3FT Twin Cable 3ft CUCBL Custom Cable NA None (1)	DC7IN FT6 DC Quick Connect 7in DC3FT FT6 DC Quick Connect 3ft FT43FT FT4 Cable 3ft TC3FT Twin Cable 3ft CUCBL Custom Cable NA None (2)
	(0) Specify length & unit of measure		(1) Refer to the following pages to select LED Strip Connectors, Splice Boxes and Wire Connectors	(2) Refer to the following pages to select LED Strip Connectors, Splice Boxes and Wire Connectors


Colour Temperature




Light Loss Factor per Colour Temperature		Maximum Run per Driver	
4000K	0%	30W	3.42ft 1.05m
3500K	8%	60W	6.84ft 2.09m
3000K	17%	75W	8.55ft 2.61m
2700K	21%	96W	10.94ft 3.34m
2400K	24%	* Tape must be refed every 30ft max to avoid voltage drop. *	
1800K	26%		

Technical Information

Parts Layout - LED Strip Connectors




Dimensions



Ordering Options


LED Strip Connectors			
Code	CNT-P92-027	Quantity	
Code	CNT-P92-028	Quantity	
Code	CNT-P92-029	Quantity	
Code	CNT-P92-030	Quantity	
Code	CNT-P92-031	Quantity	

Workshop Drawing




Technical Information

Parts Layout – Splice Boxes & Wire Connectors



Dimensions



Specifications

	CNT-P92-040	CNT-P92-041	CNT-P92-042
Rated Voltage	12-48V		
Rated Current	4A		
Working Temperature	-10°C ~ 45°C / 14°F ~ 113°F		
Temperature Resistance	105°C / 221°F		
Flame Retardant Grade	Complies with UL-94-V0		

Ordering Options

Splice Boxes			
Code	CNT-P92-040	Quantity	
Code	CNT-P92-041	Quantity	
Code	CNT-P92-042	Quantity	
Wire Connectors			
Code	CNT-P92-043	Quantity	

	CNT-P92-043
Rated Voltage	300V
Rated Current	9A
Working Temperature	-10°C ~ 45°C / 14°F ~ 113°F
Temperature Resistance	105°C / 221°F
Flame Retardant Grade	Complies with UL-94-V0
Conductor Cross Section	18 ~ 16AWG / 0.0012 ~ 0.0020in²
Max. Insulation Outer Diameter	Ø0.12in

Compatible Drivers

Click on desired Wattage for Spec Sheet.

Non-Dimmable Drivers

	Specifications	
	Universal Input Voltage: 100-277VAC	24V Constant Voltage Output, Class2
	IP66 rating, suitable for outdoor use	UL Listed
	Downloads	
	30W	96W
	60W	288W

Five-in-One Dimmable Drivers

	Specifications	
	Universal Input Voltage: 100-277VAC	24V Constant Voltage Output, Class2
	IP67 rating, suitable for outdoor use	Forward phase, Reverse phase, ELV, 0-10V, 1-10V
	Downloads	
	30W	192W
	60W	288W
	96W	

DMX Driver

	Specifications	
	Universal Input Voltage: 100-277VAC	24V Constant Voltage Output, Class2
	IP66 rating, suitable for outdoor use	Compatible with Lumen Warm Controllers
	Downloads	
	100W	

Dali 2 Driver + Lutron Athena Node

	Specifications	
	Universal Input Voltage: 100-277VAC	24V Constant Voltage Output, Class2
	IP67 rating, suitable for outdoor use	UL Listed
	Downloads	
	96W	Lutron Athena Node

Dali 2 Driver

	Specifications	
	Universal Input Voltage: 100-277VAC	24V Constant Voltage Output, Class2
	IP67 rating, suitable for outdoor use	UL Listed
	Downloads	
	96W	

Lutron Driver

	Specifications	
	Universal Input Voltage: 120-277VAC	24V Constant Voltage Output, Class2
	For indoor use only	Continuous dimming down to 0.1%
	Downloads	
	Hi-Lume Premier	

Compatible Products

Click on product names for more information.

CONNOR	DOBY	JAXSON	MYLA	OLIVIA
PALAZO MASTER	POLA	ROBERTHA	ROCCO	VENGA
VENGA SLIM	VENGA SLIM TRIMLESS	VENGA SLIM TRIMLESS PERIMETER	ARKALUX	