

PROJECT:

TYPE:

QTY:


Robertha Profile




Highlights

Mounting	Surface Mounted in groove with Brackets or Double Sided Tape
Material	Aluminum Extrusion (6063-T5)
Features	Thin, discreet, economic & easy to install
Recommended for	Small recessed application

Dimensions




Robertha Profile




Lens : CF/WF/WO/SBC

Aluminum Profile Colour



ACL - Clear Anodized



MBK - Matte Black



MWH - Matte White



CU - Custom; Specify RALK7 colour

Ordering Guide

Ex : LWRB-FIE-48IN-MBK-CF-SMDBK

Product Code	Length	Aluminum Profile Colour	Lens Options	Installation
LWRB-FIE	48IN 48in 96IN 96in	ACL Clear Anodized MBK Matte Black MWH Matte White CU Custom (1)	CF Clear Frosted Lens WF White Frosted Lens WO White Opal Lens SBC Smoked Black Lens (2) NA None	3MT 3M Tape SMDBK Surface Mounted With Bracket NA None
Each profile is provided with a pair of endcaps including: 1 X Endcap without Hole 1 X Endcap with Hole		(1) Specify RALK7 code	Refer to page 2 for Lens Options (2) For pixelation free visuals, Lumen Warm strongly recommends the use of 900lm/ft LEDs.	Supplied by Lumen Warm Length (in) Number of Mounting Brackets 0-48 2 48-84 3 84-96 4

Notes

LUMEN
WARM

 TOLL FREE 1 866 586 3692
 TEL 514 286 0227
info@lumenwarm.com

 OFFICE AND SHOWROOM
 155 Fortin Street, Suite 180, Quebec
 City, QC G1M 3M2, Canada

 LAST UPDATE
 9/10/2024

Technical Information

Lens Options



CF/WF/WO
Clear Frosted - White Frosted -
White Opal Lens



SBC
Smoke Black Lens

LED Visibility & Light Loss Factor



CF
Clear Frosted Lens
Visible
Light Loss: 8.5%



WF
White Frosted Lens
Barely Visible
Light Loss: 23.5%




WO
White Opal Lens
Diffused
Light Loss: 37.5%



SBC
Smoke Black Lens
Barely Visible
Light Loss: 70%

Installation Type


3M Tape



Details and Ordering

Code	3MT-P91-002
Mounting	Double sided tape
Quantity	Varies according to ordered length
Notes	LW recommends applying the tape to the entire length of the profile

Surface Mounted With Bracket




Details and Ordering

Code	BRK-PI3-002
Mounting	Surface Mounted in groove with brackets
Quantity	A bracket every 24in
Notes	LW recommends the use of #6 - 5/8" screws, not included, for their installation


Technical Information

Endcaps

Without Hole



With Hole



Details and Ordering

Code	ECP-PI3-025- ---	
To order additional endcaps to those already supplied by Lumen Warm, specify the desired colour by referring to the "Colour" section below.		
Material	ABS Plastic	
Colour	MBK - Matte Black MWH - Matte White	MGR - Matte Grey CU - Custom; Specify RALK7 code

Details and Ordering

Code	ECP-PI3-026- ---	
To order additional endcaps to those already supplied by Lumen Warm, specify the desired colour by referring to the "Colour" section below.		
Material	ABS Plastic	
Colour	MBK - Matte Black MWH - Matte White	MGR - Matte Grey CU - Custom; Specify RALK7 code

Available LED Strips

Static White (Click for linked document)	Lumen Output	Consumption
LWHP120	120lm/ft - 393.6lm/m	0.91W/ft - 3W/m
LWHP290	290lm/ft - 951.2lm/m	2.59W/ft - 8.5W/m
LWHP420	420lm/ft - 1377.6lm/m	3.51W/ft - 11.52W/m
LWHP700	700lm/ft - 2296lm/m	5.85W/ft - 19.2W/m
LWHP900	900lm/ft - 2952lm/m	6.59W/ft - 21.6W/m
LWHE1150	1150lm/ft - 3772lm/m	7.32W/ft - 24W/m
LWHE1400	1400lm/ft - 4592lm/m	8.78W/ft - 28.8W/m
Dim to Warm (Click for linked document)	Lumen Output	Consumption
LWD2W480	480lm/ft - 1574.4lm/m	5.27W/ft - 17.28W/m
Tunable White (Click for linked document)	Lumen Output	Consumption
LWTW220	220lm/ft - 721.6lm/m	3.05W/ft - 10W/m
LWTW300	300lm/ft - 984lm/m	4.57W/ft - 15W/m
RGBW (Click for linked document)	Lumen Output	Consumption
LWRGBW250	250lm/ft - 820lm/m	4.68W/ft - 15.36W/m